

1. Identification

Product Identifier FIZZLE Drain Opener

Other means of

identification EI-1560

Product code

Recommended use Granular drain opener. **Recommended restrictions** Professional use only.

Manufacturer information

Company name Empire Industries
Address P.O. Box 1404

Brentwood, TN 37024

Telephone (615) 315-0026 **Fax** (615) 315-0035

Emergency phone number PERS (800) 633-8253

24-hour Emergency (800) 633-8253

2. Hazard(s) Identification

Physical hazardsCorrosive to metalsCategory 1Health hazardsSpecific Target Organ ToxicityCategory 3

(single exposure-Respiratory)

Serious eye damage Category 1
Skin corrosion Category 1A

Environmental hazards

OSHA defined hazards

Label elements

Not classified.

None.



Signal word DANGER

Hazard statement Harmful if swallowed.

Causes severe skin burns and eye damage.

May be corrosive to metals

May cause respiratory irritation

Precautionary statement

Prevention Wash hands and exposed skin thoroughly after handling. Do not eat, drink, or smoke

when using this product. Do not breathe dust or mists. Wear protective

gloves/protective clothing/eye protection/face protection.

ResponseIF SWALLOWED: Immediately call a poison center/doctor/medical professional. Specific

treatment: see first aid instructions in section 4. Rinse mouth. Do NOT induce vomiting. **IF ON SKIN (or hair):** Take off immediately all contaminated clothing. Rinse skin with

water/shower. Wash contaminated clothing before reuse.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

Storage Store locked up.



Disposal Dispose of contents/containers in accordance with local/regional/national/international

regulations.

Hazard(s) not otherwise

classified (HNOC)

None.

Supplemental information None.

3. Composition/information on ingredients

Mixture Component(s)				
Chemical name	CAS number	%		
Sodium hydroxide	1310-73-2	>95		
Other components below reportable levels		1-5		

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing that does not adhere to the affected area immediately and

> wash skin with soap and water. Neutralize burns with dilute vinegar, carbonated water or citric acid. In case of eczema or other skin disorders: Seek medical attention and take

along these instructions.

Eye contact Rinse with water for at least 15 minutes. Remove contact lenses if present and easy to do

so. Immediately call a physician or transport to hospital. Permanent eye damage including

blindness could result from acute exposure.

Ingestion Rinse mouth. Get medical attention immediately. Do not induce vomiting. If vomiting

occurs, keep head low so that stomach content does not get into lungs

Most important

symptoms/effects, acute and

delayed

Can cause serious eye damage. Can cause burning sensation in affected areas. Shortness of breath, respiratory tract irritation or damage. Sodium hydroxide is extremely destructive to tissues of the mucous membranes and upper respiratory tract, eyes, and skin. Symptoms may included stinging, swelling, redness and excessive watering or blurring of the eyes and

Indication of immediate medical attention and special treatment needed Provide general support measures and treat symptomatically. Keep victim under

observation. Some cumulative symptoms may be delayed.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions

to protect themselves. Wash contaminated clothing before reuse. Use with extreme

caution.

5. Fire-fighting measures

Suitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO₂).

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from During fire, gases hazardous to health may be formed.

the chemical

Special protective equipment

and precautions for firefighters

Self-contained breathing apparatus and full protecting clothing must be worn in case of fire.

Fire-fighting

Move containers from fire area if you can do so without risk.

equipment/instructions

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.



6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of vapors or mists. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

This product is miscible in water.

Large spills: Place the material in containers using a broom or shovel. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small spills: Sweep up and put into containers. Clean surface thoroughly to remove residual contamination.

Never return spills to original container for re-use. For waste disposal, see section 13 of the

SDS

Environmental precautions Avoid discharge/dispose onto the ground or into areas not consistent with package

labeling.

7. Handling and storage

Precautions for safe handling

Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in original tightly closed container. Store away from incompatible materials (see

section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value
Sodium Hydroxide	PEL	2 mg/m ³

US ACGIH Threshold Limit Values

NIOSH Pocket Guide

ComponentsTypeValueSodium HydroxideCeiling-REL2 mg/m³

Biological limit values No information.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels to an acceptable level. It is recommended that users of this product perform a risk assessment to determine the appropriate personal protective equipment.

Individual protection measures, such as personal protective equipment

Material Name: FIZZLE Drain Opener Page 3 of 8 SDS US



Eye/face protection
Skin protection

Avoid contact with eyes. Wear safety glasses with side shields (or goggles).

Hand protection The use of gloves impervious to the specific material handled is advised to prevent skin

contact. Users should check with manufacturers to confirm the breakthrough performance of their products. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Suggested protective materials: Nitrile and PVC rubber.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is

recommended. Depending on exposure and use conditions, additional protection may be necessary to prevent skin contact including use of items such as chemical-resistant boots,

aprons, arm covers, hoods and/or coveralls.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygieneconsiderations
When using do not smoke or use chewing tobacco. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or

smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical State Granular solid
Color Gray/dark red
Odor Sassafras.
Odor threshold Not available.
pH 14 (10% solution)
Melting/freezing point Not available.
Initial boiling point and Not applicable.

boiling range

Flash point Not applicable.

Evaporation rate Not available.

Flammability Not available.

Flammability Limits

Upper Not available.
Lower Not available.
Vapor pressure Not available.
Vapor density Not available.

Specific gravity (water=1) 2.13 g/cm³ (estimated)

Solubility in water Soluble.

Partition coefficient Not applicable

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

10. Stability and reactivity

Reactivity This product is stable and non-reactive under normal conditions of use. **Chemical stability** Material is stable under normal conditions. Store in a cool dark place.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Material Name: FIZZLE Drain Opener Page 4 of 8 SDS US



Conditions to avoid Avoid storage in elevated temperatures.

Incompatible materials Acids, oxidizers, amines, zinc and alkaline metals. Product will generate heat when mixed

with water.

Hazardous decomposition

products

No hazardous decomposition products occur. In case of fire see section 5.

11. Toxicological information

Information on likely routes

of exposure

Ingestion Do not ingest. Harmful if swallowed.

InhalationDo not inhale. May cause damage to the upper respiratory tract.Skin contactCauses severe skin burns. See section 8 for personal protection.Eye contactCauses serious eye damage. See section 8 for personal protection.

Symptoms related to the Burning sensation, physical, chemical and extremely destruct

Burning sensation, coughing, wheezing, shortness of breath. Sodium hydroxide is extremely destructive to mucous membranes and upper respiratory tract, eyes, and skin.

toxicological characteristics extremely destructive to mucous membranes and upper respiratory tract, eyes, and skin

Acute toxicity Harmful if swallowed.

Product FIZZLE Drain Opener (CAS mixture)				
Exposure Classification	Route and Species	LD ₅₀		
Acute	Oral, rat	> 700 mg/kg (Literature)		
*Estimates for product may be based on additional component data not shown				

Skin corrosion/irritationCauses severe skin burns.Serious eye damage/ irritationCauses serious eye damage.

Respiratory sensitization Not considered a respiratory sensitizer.

Skin sensitization Not considered a skin sensitizer.

Germ cell mutagenicity

No data available to indicate product or any

components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not considered a carcinogen.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) Not Listed.

Reproductive toxicityNo data available.Specific target organ toxicity – single exposureNot classified.Specific target organ toxicity – repeated exposureNo data available.Aspiration hazardNo data available.

12. Ecological information

Ecotoxicity				
Product FIZZLE Drain Open	er			
Aquatic Receptor	Species	Test Threshold(s)		
Fish	Fathead minnow (Pimephales promelas)	LC ₅₀ = 45 mg/L (estimated)		
Crustacea	Daphnia Magna	EC ₅₀ = 40 mg/L (estimated)		

^{*}Estimates for product may be based on additional component data not shown

Specific toxicity threshold cannot be derived as the potential effects are highly dependent upon the pH of the receiving water and its buffer capacity highly variable.

Persistence and degradability No data available.

Bioaccumulative potentialThis product is a highly water-soluble inorganic substrate and will not

accumulate in biological systems



Partition coefficient n-octanol/water (log Kow)

Mobility in soil

Not applicable

No data available. Listed components are inorganic and highly water-

soluble. In aqueous medium, the listed chemical(s) will readily dissociate into ionic molecules that will be weakly adsorbed onto organic matter particles. These components are expected to exhibit moderate to high mobility in saturated and semi-saturated soils.

Other adverse effects Harmful to aquatic and terrestrial life. The pH of this product may cause it to harm aquatic

life in high concentrations.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose

of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the

waste disposal company.

Waste from residues/unused

product

Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner.

(see: Disposal instructions).

Empty containers should be taken to an approved waste handling site for recycling or **Contaminated packaging**

disposal. Since emptied containers may contain product residue, follow label warnings

even after container is emptied.

14. Transport information

DOT

UN number UN1759

UN proper shipping name Corrosive solids, n.o.s. (contains: Sodium hydroxide)

Transport hazard

class(es)

Class 8 Subsidiary risk **Packaging group** Ш Marine pollutant No

Special precautions for user

Read safety instructions, SDS, and emergency procedures before handling. Transport in bulk according Not intended to be transported in bulk.

to Annex II of MARPOL 73/78 and the IBC Code **DOT Label/Placard**



15. Regulatory information

US federal regulations

SDS US Material Name: FIZZLE Drain Opener Page 6 of 8

EMPRE

SAFETY DATA SHEET

SARA 302 Extremely hazardous substance Not listed.

SARA 304 Emergency release notification Not listed.

SARA 311/312 Hazard Categories

Immediate Hazard - Yes
Delayed Hazard - No
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - Yes

SARA 313 (TRI reporting) Not listed.

California Proposition 65 California Safe Drinking Water and Toxic Enforcement Act of 1986

This product is not known to contain any chemicals currently listed as carcinogens or reproductive toxins under California Proposition 65 at levels which would be subject to

threshold determination and Safe Harbor notification (1/2019)

16. Other information, including date of preparation or last revision

Issue date 12/5/2019

Revision date

Version # 1

HMIS® ratings Health: 3

Flammability: 0 Physical hazard: 2



ALKALINE

NFPA ratings Health: 3

Flammability: 0
Instability: 2





Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, and have been obtained from resources believed to be reliable. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal, and release and is not to be considered a warranty or quality specification. The information related only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified by the text.

Revision information

First Issue

Material Name: FIZZLE Drain Opener